

Fenestra Too!

PERFORMANCE FABRIC

Grade 8

Click on image to order memo sample.



66130 Bohemia



66131 Marsh



66132 Lark



66133 Serrano



66138 Mariana



66135 Vindaloo

Fenestra Too!

PERFORMANCE FABRIC

Click on image to order memo sample.

Grade 8



66136 Sapphire



66137 Ridge



66134 Cove

Fenestra Too!

PERFORMANCE FABRIC

Grade 8

Performance Summary

- Enhanced soil + stain resistance
- Enhanced abrasion resistance
- Fluid barrier
- Contains an antimicrobial agent
- Bleach-solution cleanable

Environmental

- GREENGUARD Gold Certified
- LBC Red List Free
- Recycled content
- Non PFOA Stain Resistance
- No added flame retardants

Cleaning and Maintenance

Cleaning Code: **(W)** Clean with water-based foam or water-based cleaners only. Do not use solvents. We recommend using a professional cleaning service.

Bleach solutions of up to 10% may be used for more difficult stains.

Dye lots may vary slightly.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Specifications



Content	65% Post Consumer Recycled Polyester, 35% Polyester
Finish	Crypton® Non-PFOA Soil & Stain Protection
Backing	Crypton® Fluid Barrier
Weight	14.65 oz./lin. yd. ± 1.0 oz.
Width	54 inches
Repeat	Horizontal: 15.0 inches, Vertical: 3.0 inches, directional
Roll Size	55 yards

Performance Characteristics

Abrasion Resistance ASTM D-4157	Exceeds 63,000 double rubs - heavy duty
Break Strength ASTM D-5034	Warp: 215 lbs. min., Fill: 213 lbs. min.
Tear Strength ASTM D-2261	Warp: 16 lbs. min., Fill: 31 lbs. min.
Seam Slippage ASTM D-4034	Warp: 106 lbs. min., Fill: 125 lbs. min.
Brush Pilling ASTM D-3511	Class 5.0 min.
Colorfastness to Light AATCC-16	40 Hours, Class 4.0
Crocking AATCC-8	Dry: Class 5.0, Wet: Class 4.5
Fluid Barrier	Crypton® Integrated Fluid Barrier
Antimicrobial	Crypton® fabric protection features silver ion technology which inhibits the growth of microbes on the protected surface.

Flammability*

California Technical Bulletin 117-2013 Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1



This product is produced using 65% recycled fiber.



Stinson®

C.F. Stinson, LLC
2849 Product Drive
Rochester Hills, MI 48309

P 800 841 6279

F 248 299 3884

cfstinson.com