Lara

Grade 2

⁴





LRA52 Blush





LRA54 Tonic





LRA53 Opulent







Stinson[®]

Stinson






LRA60 Buttercup





(A56 Marmalade





LRA61 Salsa




LRA57 Miso



Grade 2




LRA62 Red Earth



LRA64 Pear





LRA66 Spice



LRA63 Angora



LRA65 Marigold




LRA67 Tamale





LRA68 Vicuna




LRA70 Cashew




LRA72 Port



LRA69 Taupe




LRA71 Plum



LRA73 Pumice





LRA74 Timberland




LRA76 Velvet



LRA78 Barre



LRA75 Tawny



LRA77 Cordovan




LRA79 Cloud



Grade 2

⁴




LRA80 Tint




LRA82 Titanium






LRA84 Blue Ice



LRA81 Athens



LRA83 Minty











LRA86 Gate




LRA88 Hydro




LRA90 Bahama



LRA87 Haze



LRA89 Champion




LRA91 Kitten



Grade 2

⁴ ⁴



LRA92 Mink



LRA94 Patriot






LRA96 Hearth



LRA93 Clover



LRA95 Tranquil



LRA97 Barista




Grade 2



LRA98 Vine



LRA100 Wizard



LRA102 Espresso



LRA99 Mid-Blue



LRA101 Tempest



LRA103 Sherwood



<u>4</u> ⁴




LRA104 Evening



LRA106 Java



LRA105 Mystery



LRA51 Bisque



Performance Summary

- Enhanced soil + stain resistance
- Enhanced abrasion resistance
- CFFA-Healthcare-201: Certified
- Fluid barrier
- Bleach-solution cleanable
- Enhanced fade resistance

Environmental

- GREENGUARD Certified
- REACH Compliant
- RoHS Compliant
- No PFAS, fluorocarbons or perfluorinated compounds
- No added flame retardants
- · No added antimicrobials
- Formulated without Phthalates

Cleaning and Maintenance

Cleaning Code: (W) Clean with water-based foam or water-based cleaners only. Do not use solvents. We recommend using a professional cleaning service.

Bleach solutions of up to 10% may be used for more difficult stains.

Dye lots may vary slightly.

* This term and any corresponding data refer to the typical performance in the tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

** Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

Specifications	
Content	Vinyl Surface with Polyester Backing
Finish	Advanced Soil and Stain Resistant Top Coat
Backing	Polyester Fabric
Weight	28.0 oz./lin. yd. ± 1.0 oz.
Width	54 inches
Roll Size	40 yards
Performance Characteristics	
Abrasion Resistance** ASTM D-4157	Exceeds 1,300,000 double rubs - heavy duty
Adhesion CFFA-3	Warp: 4.0 lbs. min., Fill: 4.0 lbs. min.
Break Strength CFFA-17	Warp: 85 lbs. min., Fill: 75 lbs. min.
Tear Strength CFFA-16	Warp: 20 lbs. min., Fill: 27 lbs. min.
Seam Slippage CFFA-14	Warp: 35 lbs. min., Fill: 30 lbs. min.
Colorfastness to Light CFFA-2	650 Hours, Class 4.0
Fluid Barrier	Inherent Fluid Barrier
Flammability*	
California Technical Bulletin 117-2013 Section 1	Passed
UFAC	Class 1
NFPA 260	Class 1
BIFMA	Class 1
REDUCED ENVIRONMENTA IMPACT	This product is formulated without phthalates.





C.F. Stinson, LLC 2849 Product Drive Rochester Hills, MI 48309

P 800 841 6279F 248 299 3884

cfstinson.com